

### Track Condition

**Composition:**  Asphalt  Carpet  
**Environment:**  Indoor  Outdoor  
**Surface:**  Smooth  Both  Bumpy  
**Traction:**  Low  Medium  High  
**Size:**  Tight  Mixed  Open  
**Track Temp.:** \_\_\_\_\_ **Air Temp.:** 75

### Electronics

**Motor:** 4.5T **Timing:** \_\_\_\_\_  
**ESC:** \_\_\_\_\_ **Battery:** \_\_\_\_\_  
**Spur:** 107 **Pinion:** 25 **Ratio:** \_\_\_\_\_

### Aerodynamics

**Body:** Type S Pro Lite **Wing:** LTCR LW

Front	Shocks	Rear
<u>RSD Black/GZ2.35</u>	<b>Spring -</b> <u>RSD Black/GZ2.35</u>	
<u>30</u>	<b>- Oil -</b> <u>30</u>	
<u>XRAY pss SLP</u>	<b>- Piston -</b> <u>Xray PSS SLP</u>	
<u>0</u>	<b>- Rebound (%) -</b> <u>0</u>	
	<b>- Foam Inserts -</b>	
	<input type="checkbox"/> ULP <input checked="" type="checkbox"/> SLP <input type="checkbox"/> STD	

### Anti-Roll Bar

1.0 1.2

### Tires & Wheels

**Tires:** Elexis 36  
**Inserts:** \_\_\_\_\_  
**Rims:** \_\_\_\_\_  
**Additive:** \_\_\_\_\_  
**Additive Time:** \_\_\_\_\_





### Transmission

Gear  Ball - Diff -  Gear  Ball  
7500 small shims **- Oil -** \_\_\_\_\_  
**- Oil Weight (Grs) -** \_\_\_\_\_  
AMX Diff **- Settings -** \_\_\_\_\_  
 Spool

*Long Arm Conversion. Arms oriented with 1mm inset shock mount holes being used. High bearing carriers all around. Rear Bulkhead brace installed.*


### Front

**Toe:** 1 out  
**Camber:** 2.5  
**Caster:** 4  
**Droop:** 2.0 ORH  
**Rideheight:** 5.2  
**Wheel Hex:** STD +0.5shim  
**Lower arms:**  Alloy  Carbon  
**Caster Plate:**  1-piece  2-piece



Shim: 2



Shim: 1



**Steering:**  
 Gizmo  
 LS2 (Ackermann: Bell Cranks)



### Rear

**Toe:** 2.5  
**Camber:** 2.0  
**Caster:** -4  
**Droop:** 2.5 ORH  
**Rideheight:** 5.4  
**Wheel Hex:** Std +0.5 shim  
**Lower arms:**  Alloy  Carbon  
**Caster Plate:**  1-piece  2-piece



Shim: 2

Shim: 2



**Chassis:**  Alloy  Carbon

